

TRANS TECH CONSULTANTS

Environmental Compliance Services Engineers • Geologists • Architects License # 697833 (A-Haz)

November 9, 2005 Job No. 3034.01

Mr. Jack Tipple Tipple Motors, Inc. P.O. Box 855 Ferndale, California 95536

Subject:

Summary Report of Investigation / Monitoring Well Installation

Tipple Motors, Inc., 524 Main Street, Ferndale, California

LOP# 12052

Dear Mr. Tipple:

This report presents the results of the recent investigation performed at the subject site. The site is approximately located as shown on the attached Site Location Map, Plate 1. The scope of work performed was based on a July 5, 2005 letter from Mr. Mark Verhey with the Humboldt County Department of Health and Human Services - Division of Environmental Health (HCDHHS-DEH).

Site Description

The site is located in a light commercial and retail district within the city limits of Ferndale, California. Residential properties are present within 50 feet of the site. The site is generally flat and currently contains a single story structure that houses an automotive repair facility, a real estate office, and a service station with an above ground gasoline storage tank and fuel dispenser. The site is bordered to the north by Main Street, to the south by a gravel lot/alley and residential housing, to the east by the Ferndale Post Office and commercial buildings, and to the west by Washington Street. The site and general site features are shown on the attached Site Plan, Plate 2.

Local Geology and Hydrogeology

Published geologic data reviewed indicates the site is underlain by estuarine deposits which consist of silty sands and clayey silts. Underlying the estuarine deposits is the Hookton Formation, consisting of weakly consolidated marine sands with minor pebbly beds and clay strata. Our previous test borings encountered estuarine deposits to the depths explored, consisting mainly of grey silty clay with occasional interbeds of silt and clayey sand.

Calculated groundwater elevation measurements indicate that ground water at the site is at shallow depth, ranging from about 3.8 to 5.9 feet below ground surface (BGS), with the direction of flow generally to the southeast.

Background

It is our understanding that on September 1978, two 4,000-gallon gasoline USTs were installed at the site. Two 550-gallon gasoline USTs were abandoned in-place on the same date by filling them with pea gravel and topping them off with a concrete slurry. Soil samples were collected in June of 1988 to fulfill HCDEH tank closure requirements. Analysis of these samples detected total petroleum hydrocarbons (TPH) as gasoline at concentrations as high as 6,100 milligrams per kilogram (mg/Kg). In an April 19, 1993 letter, Mr. Jim Clarke of HCDEH requested a soil and groundwater investigation be implemented at the site.

In November and December 1993, TTC performed a preliminary site investigation which consisted of drilling seven soil borings (SB-1 through SB-7) and installing two groundwater monitoring wells (MW-1 and MW-2) in the vicinity of the abandoned USTs. Soil boring and well locations are approximately shown on Plate 2. The results of our preliminary investigation were presented in a June 16, 1995 Summary Report.

In July and August of 1996, TTC performed additional investigation by drilling nine additional test borings (SB-8 through SB-17) and converting three of the borings (SB-15 through SB-17) to monitoring wells MW-3 through MW-5. The results of our investigation were summarized in a December 3, 1996 Summary Report.

On September 25 through 29, 1997, Haberstock Construction of Fortuna, California, removed the two active 4,000-gallon and two inactive 550-gallon USTs located on the site. During the excavation procedures, the gasoline pump island, hydraulic auto hoist, and approximately 590 cubic yards of contaminated soil were removed from the vicinity of the former USTs. The results of the excavation activities and laboratory sample results were presented in our October 24, 1997 Summary Report. Approximate excavation limits and former tank locations are shown on Plate 2.

On September 29 through October 1, 1997, Haberstock Construction backfilled the excavation with clean imported fill. Stabilization fabric was placed into the excavation at 8 feet below ground surface (BGS). TTC applied 630 pounds of Oxygen Release Compound (ORC) to the backfill material, placed from the bottom of the excavation to the top of the capillary fringe zone, estimated at about 4 feet BGS.

On October 7 and 8, 2002, TTC and Clear Heart Drilling of Santa Rosa, in order to further investigate and delineate the extent of the groundwater impact in the northwesterly, westerly, and southwesterly directions, advanced five soil borings (SB-18 through SB-22) and two monitoring wells (MW-6 and MW-7)at the approximate locations shown on Plate 2.

On October 30, 2004, TTC advanced one soil boring (SB-23) in order to further delineate the extent of the groundwater impact in the easterly direction underneath the existing structure.

The soil and groundwater samples collected during the November/December 1993 preliminary site investigation and the July/August 1996 additional site investigation were analyzed for total petroleum hydrocarbons (TPH) as gasoline, the volatile organic compounds: benzene, toluene,



ethylbenzene, and xylenes (BTEX) and total lead (Pb) using EPA Test Methods 8015/8020/7421. The results are presented in units of milligrams per kilogram (mg/kg) and micrograms per kilogram (μ g/kg) for soil and milligrams per liter (mg/L) and micrograms per liter (μ g/L) for water.

Soil and groundwater samples collected during the October 2002 and October 2004 additional site investigations were analyzed for TPH as gasoline, TPH as diesel, BTEX, and the additional oxygenated fuel additives including methyl tert-butyl ether (MtBE) and lead scavengers including 1,2-dichloroethane by EPA Test Methods 8015/8020/8260. The results are presented in units of mg/kg for soil and μ g/L for water.

Historic soil sample analytical results are presented in Appendix A. Historic groundwater analytical results from the aforementioned site investigations are presented in Appendix B.

Field Activities

On July 19, 2005, TTC staff were onsite to advance one monitoring well, MW-8, for the purpose of delineating soil and groundwater impact under the existing structure in the proximity of soil boring B-8. In addition, the monitoring well will provide data necessary to determine the efficacy of the remediation system. The approximate location of MW-8 is shown on Plate 2.

After an area of the existing flooring was removed for access, MW-8 was advanced using a hand auger. Our geologist observed the augering procedures and collected soil samples for classification every six inches and performed petroleum hydrocarbon screening with a PID. Soil samples were classified according to the Unified Soil Classification System and recorded on the attached Boring Log, MW-8, Plate 3. In general, the soils encountered consisted of light brown to gray clayey silts and clayey sandy silts from the surface down to approximately 13 feet BGS. The clayey/sandy silts were underlain to approximately 15 feet BGS by a gray silty clay. Initial free water was encountered at approximately 5 feet BGS and the final depth of hand augering reached approximately 15 feet BGS. Grab soil samples collected for chemical analysis were obtained in areas of obvious contamination, just above free groundwater, and at pronounced changes in soil type. Soil samples collected for laboratory chemical analysis were recovered in pre-cleaned stainless steel tubes. Upon recovery, the sample tubes were then capped with non-adhesive Teflon tape and plastic caps, labeled, and placed on ice. In addition, a secondary soil sample was immediately extracted and placed in a preserved VOA vial pursuant to EPA 5035 protocol. Soil samples were transported under chain of custody documentation to Alpha Analytical Laboratories for chemical analysis.

Sampling equipment was cleaned with a phosphate-free detergent solution and double rinsed with clean water. Rinsate water and soil cuttings generated by the investigation were stored onsite in 55 gallon DOT-approved drums, pending disposal.

Monitoring Well Construction

The well was constructed in general accordance with State and local guidelines and with the attached Monitoring Well Completion Diagram, Plate B. The monitoring well extends approximately 10 feet below free groundwater and extends to total depth of approximately 15 feet BGS. The well was constructed of 1-inch diameter, Schedule 40 PVC casing. The screened portion of the wells has 0.020-inch machined slots with Lone Star Sand #2/12 placed in the annular space. The screened portion of the wells extends from the bottom of the well to approximately 5 feet BGS. The sand pack extends from the bottom of the wells to approximately 1 foot above the screened portion. A 1-foot thick bentonite seal was placed above the sand pack, and the remainder of the well annulus space was filled with a cement grout seal. The well casing extends to approximately 2 feet above ground and was fitted with a water proof locking cap. The existing floorboards were then replaced in a manner that would allow access for monitoring and sampling.

Monitoring Well Development and Sampling

The monitoring well MW-8 was developed on July 21, 2005 by surging and bailing until the produced water became relatively sediment free. On September 22, 2005, groundwater samples were collected from the monitoring wells (wells) MW-1 through MW-8 at the subject site as part of the ongoing semi-annual sampling schedule. Prior to sampling, the static water level was measured and checked for the presence of free product using an oil/water interface probe. No free product was detected during this monitoring event. To produce representative samples prior to sampling, well MW-8 was purged of approximately three well casing volumes using a disposable bailer. In addition, indicator parameters including the temperature, pH, and conductivity were measured during purging and recorded on the attached Groundwater Field Sampling Form, Appendix C. The water level was allowed to sufficiently recover prior to sample collection. Groundwater samples were collected using a new disposable bailer and transferred to the appropriate containers supplied by the laboratory. The groundwater samples were labeled, stored on ice, and transported under Chain-of-Custody documentation to Kiff Analytical LLC (Kiff) of Davis, California for chemical analysis. Purge groundwater generated during the sampling of the wells was stored onsite in 55-gallon DOT approved drums, pending disposal. Monitoring and analytical results for the September 22, 2005 sampling event will be published under separate cover as 3rd Quarter 2005 Monitoring Report.

Gradient Determination

The top of the well casing on MW-8 will need to be surveyed to 0.01 of a foot relative to mean sea level as soon as possible. The location of the well will also be surveyed utilizing Global Positioning Systems (GPS) to within sub-meter accuracy. Water level measurements will be collected from all seven wells and will be used with the survey data to evaluate the direction of groundwater flow and the slope of the potentiametric surface in the direction of flow. The TOC elevation data, the GPS data and the water level elevation data will also be submitted electronically to the Geotracker database as required by Title 23, Division 3, Chapter 16, Article 12 of the California Code of Regulations.



Laboratory Chemical Analysis

Two soil samples and a groundwater sample collected from well MW-8 were submitted for laboratory chemical analysis. The samples were analyzed for TPH as gasoline(g), TPH as diesel(d), BTEX, the five oxygenated fuel additives including MtBE, and lead scavengers by EPA Test Methods 8015/8260. One soil sample was collected and preserved using EPA 5035 protocols. The analytical results of the soil and groundwater samples collected are tabulated in units of milligrams per kilogram (mg/kg) for soil and micrograms per liter (μ g/L) for groundwater. The Alpha laboratory analytical report for soil samples collected on July 19, 2005, including the chain of custody documentation is presented in Appendix D. The Kiff laboratory analytical report for groundwater samples collected on September 22, 2005, including the chain of custody documentation is presented in Appendix E.

Soil Sample Results

Jon Dain	pic ixesuits							
Date	Sample ID	TPH-g	TPH-d	B	Ā	E	X	MtBE
					mg/kg			
07/10/05	MW-8-5	3,000	580*	<17	<17	<17	<17	<17
07/19/05	MW-8-14.5	5.9	5.7	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050**

< = not detected at or above the indicated laboratory detection limit.

Groundwater Sample Results

Date	Sample ID	TPH-g	TPH-d	В	Ŧ	E	X	MtBE
					μg/L			
09/22/05	MW-8	12,000	<3,000	680	58	400	390	<2.0**

< = not detected at or above the indicated laboratory detection limit.

Discussion

The analysis results confirm petroleum hydrocarbon impact in shallow soils and groundwater within the interior of the building footprint. Further, the current data along with previous investigation data indicate that the zone of impact extends not only beneath the office area, but also beneath the garage area. We will continue to monitor and sample groundwater in well MW-8 on a monthly basis to evaluate the remediation system and determine the rate of degradation of the contaminant plume.

Based upon requests made in the July 5, 2005 letter from Mr. Mark Verhey of the HCDHHS-DEH, we are scheduled to install another monitoring well in the vicinity of soil boring B-23. The work is being performed in conjunction with ongoing site remediation activities. Those activities are being reported under separate cover.



^{* =} results in the diesel organics range are primarily due to overlap from a gasoline range product.

^{** =} di-isopropyl ether detected at 0.65 mg/kg and 1,2-dichloroethane detected at 0.028 mg/kg.

^{* =} results in the diesel organics range are primarily due to overlap from a gasoline range product.

^{** =} additional oxygenated fuel additives and lead scavengers detected (see laboratory report).

We appreciate the opportunity to be of service to you and trust this report provides the information you require at this time. If you have any questions, or need any additional information, please don't hesitate to contact us at (707) 575-8622 or www.transtechconsultants.com.

Sincerely,

TRANS TECH CONSULTANTS

Brian R. Hasik Staff Geologist

Bill C. Wiggins, PE

Registered Civil Engineer

ROI_3034_01_110905

cc:

Attachments: Plate 1, Site Location Map

Plate 2, Site Plan

Plate 4, Well Grant Line B

Plate 4, Well Completion Diagram MW-8 Appendix A, Historic Soil Sample Results

Appendix B, Historical Site Investigation Groundwater Analytical Results

Appendix C, Groundwater Field Sampling Form - MW-8

Appendix D, Alpha Analytical Laboratories Report dated August 5, 2005

Appendix E, Kiff Analytical LLC Report dated October 3, 2005

Exp. 12-31-06

Mr. Mark Verhey, CEG

Humboldt County Department of Public Health


Division of Environmental Health

100 H Street, Suite 100 Eureka, California 95501

North Coast Regional Water

Quality Control Board

5550 Skylane Boulevard, Suite A Santa Rosa, California 95403





930 SHILOH RD., BLDG 44, SUITE J WINDSOR, CA 95492 PHONE: 707-575-8622 FAX: 707-837-7334


SITE LOCATION MAP

TIPPLE MOTORS 524 MAIN STREET


FERNDALE, CALIFORNIA


PLATE:

	T					
DRAWN BY:	DWG NAME:	APPR. BY:	JOB NUMBER:	W.O. NUMBER:	REVISIONS:	DATE:
PSC	3034.01 SLM	LSH	3034.01	A-264		10/9/03



Log Dril	ged I St	By art	9/05 : BR Time:	H e: 1:							BOR	8 8). 	Se	e U	Inifi	ed S	ion — See Site Plan Soil Classification System (USCS) and information not noted.
Dril Dril Sar	ler's ling nplir nme	No Me	ime: thod: Meth	BRI : <u>HA</u> od: _	AN I ND GRA	HASI AUG B						 		Cer Aug	nen ger	t 🔲 Dep	th,	Y⊠ N☐ if no, boring filled with: Bentonite: Cement☐ Grout☐ Chips☒ ft:15 Total Depth, ft:15 it., ft:NA Temp Screen, ft:NA
Sample	Sample Condition	Inches Recovered	C = CMSSS SP = Std. Pin	Blows / 6 in.	Initial Free Water	Static Water	PID (ppm) maximum, not stabilized	Odor	Discolored	USCS Soil Class.	Depth in Feet	Graphic Log		Estimated Gravel, %	Estimate Sand, %		Estimated	
								No YES	No YES		1 2 3					60	40	LIGHT BROWN MOIST CLAYEY SILT
							126				- 5 - 6 - 7				30	50	20	GRAY WET CLAYEY SANDY SILT
							21	?	?	ML	9 10 11				40	50	10	GRADES INTO TAN/GRAY MOTTLED SATURATED SANDY SILT ODOR DECREASES
							4.6	? No	? No	CL	12 13 14 					40	60	BECOMES GRAY WET SILTY CLAY
DRA	ONE:	30 S V 707-	HILOH MNDSC -575- DWG 1	RD., OR, C. -8622 NAME	BLDG A 954 FAX	44, 192 : 707			f: J	OB NU	16		W.(TIF 524 FE	PLE MA RNE	MC IN S DALE	G MW-8 OTORS STREET E, CA IONS: DATE: 7/26/05







Appendix A: Historic Soil Sample Analytical Results

Date	Sample	Depth	TPH as Gasoline	В	T	E	x	Pb
	ID	feet	mg/Kg		iră	/Kg		mg/Kg
	SB-1	5.5	1.2	73	5.2	20	15	90
11/16/93	SB-2	5.5	1,400	<250	<250	13,000	<250	12
	MW-1	7.5	<1	<2.5	<2.5	<2.5	<2.5	4.6
	MW-2	7.0	3.4	650	20	130	190	4.7
	SB-3	4.0	570	5,200	1,100	7,400	32,000	10
11/17/93	SB-4	4.0	170	<250	<250	1,400	1,700	11
	SB-5	7.0	3.1	980	4.5	25	25	4.3
	SB-6	4.0	4.5	<2.5	<2.5	<2.5	<2.5	72
	SB-7	6.5	600	1,500	<500	3,500	2,500	5.0
	SB-8	11.5	1,400	7,800	4,800	35,000	16,000	10
	SB-9	4.5	420	<250	390	<250	<250	8.6
7/10/96	SB-9	15.5	<1.0	<2.5	<2.5	<2.5	<2.5	5.6
ļ	SB-10	12.0	1.8	200	9.4	15	20	6.4
L	SB-11	12.0	1.6	65	5.4	16	9.2	6.7
Į	SB-13	7.5	1.0	87	<2.5	5.4	6.0	5.1
	SB-14	6.5	60	56	<2.5	72	61_	6.2
8/16/96	SB-17	6.0	<1.0	<2.5	<2.5	<2.5	<2.5	5.8
< = No	ot detected al	bove the indi	cated laborator	y reporting li	mit.			

Appendix A continued

Date	Sample ID	TPH- gasoline	TPH- diesel	В	T	E	x	MtBE
					mg/Kg	<u> </u>		
	MW-6-4'	<1.0	<5.0	<0.005	<0.005	<0.005	<0.015	<0.025
	MW-6-9'	<1.0	<5.0	<0.002	<0.002	<0.002	3.9	<0.002*
	SB-18-5'	<1.0	<5.0	<0.005	<0.005	< 0.005	<0.015	<0.025
10/07/02	SB-18-9'	<1.0	<5.0	<0.002	<0.002	<0.002	3.8	<0.002
10,0,00	SB-19-4'	<1.0	<5.0	<0.002	<0.002	<0.002	3.0	<0.002
	SB-19-9'	<1.0	<5.0	<0.005	< 0.005	<0.005	<0.015	<0.025
	MW-7-4'	<1.0	<5.0	<0.005	<0.005	<0.005	<0.015	<0.025
	MW-7-9'	<1.0	<5.0	<0.002	<0.002	<0.002	2.8	<0.002
	SB-20-3.5'	<1.0	<5.0	<0.005	<0.005	<0.005	<0.015	<0.025
10/08/02	SB-20-7'	<1.0	<5.0	<0.002	<0.002	<0.002	3.7	12*
	SB-21-4'	<1.0	<5.0	<0.002	<0.002	<0.002	3.9	<0.002
	SB-21-6'	<1.0	<5.0	<0.005	<0.005	<0.005	<0.015	<0.025
	SB-22-4'	<1.0	<5.0	<0.002	<0.002	<0.002	3.7	<0.002
	SB-22-9'	<1.0	<5.0	<0.005	<0.005	< 0.005	<0.015	<0.025
	SB-23-4.5	3,600	410**	<43	<43	76	430	<43
10/30/04	SB-23-7	52	3.9	1.7	<0.87	1.2	4.8	<0.87
	SB-23-8	3.0	<1.0	< 0.0031	<0.0031	<0.0031	<0.0031	<0.0031***

^{*} Additional oxygenated fuel additives were detected above the laboratory detection limit, see laboratory report for details.

** = results in the diesel organics range are primarily due to overlap from a gasoline range product.

*** = di-isopropyl ether detected at 0.0035 mg/kg.



Appendix B: Historic Site Investigation Groundwater Analytical Results

Date	Sample	TPH as Gasoline	В	T	E	x	Рь
	ID	mg/I		IIS	Л.		mg/L
12/27/93	MW-1	0.07	<0.5	<0.5	<0.5	<0.5	<0.002
	MW-2	6.3	1,100	78	16	610	0.030
	SB-8	80	5,500	630	3,400	1,200	NA
07/10/96	SB-9	16	790	52	280	190	NA
	SB-10	0.78	99	1.9	2.0	3.8	NA
07/10/20	SB-11	0.60	19	2.0	2.2	2.2	NA
	SB-12	<0.05	<0.50	<0.50	<0.50	<0.50	NA
	SB-13	2.6	330	15	24	15	NA
	MW-1	0.06	<0.5	<0.5	<0.5	<0.5	0.012
	MW-2	11	3,900	200	550	1,100	0.012
08/30/96	MW-3	<0.05	<0.5	<0.5	<0.5	<0.5	<0.002
	MW-4	0.12	4.9	<0.5	0.6	0.7	0.004
	MW-5	<0.05	<0.5	<0.5	<0.5	<0.5	<0.002

Not analyzed.

Appendix B continued

Date	Sample ID	TPH- gasoline	TPH- diesel	В	r	E	X	MtBE	1,2- dichloroethane
						μg/L			
10/07/02	SB-18	<50	<50	<1.0	<1.0	<1.0	<1.0	<1.0	NA
10/07/02	SB-19	<50	<50	<1.0	<1.0	<1.0	<1.0	<1.0	NA
	SB-20	78	<50	<1.0	<1.0	<1.0	<1.0	64*	NA
10/08/02	SB-21	88	<50	<1.0	<1.0	<1.0	<1.0	2.3	NA
	SB-22	<50	<50	<1.0	<1.0	<1.0	1.0	<1.0	NA
	MW-1	<50	<65	<0.30	<0.30	<0.50	<0.50	38*	<50
	MW-2	29,000	1,600	6,000	110	960	1,200	<50*	99
	MW-3	<50	<65	<0.30	<0.30	<0.50	<0.50	<0.50*	<0.50
12/02/02	MW-4	350	320	25	0.73	1.9	1.0	45*	1.0
	MW-5	190	320	0.35	<0.30	0.58	<0.50	<0.50*	<0.50
	MW-6	<50	<65	<0.30	<0.30	<0.50	<0.50	<0.50*	<0.50
	MW-7	<50	<100	<0.30	<0.30	<0.50	<0.50	0.61	<0.50
10/30/04	SB-23	28,000	3,500**	2,100	390	1,500	3,500	<50	<43

^{* =} Additional oxygenated fuel additives were detected above the laboratory detection limit, see laboratory report for details.

^{** =} results in the diesel organics range are primarily due to overlap from a gasoline range product.



GROUNDWATER FIELD SAMPLING FORM

			WELL INFO	RMATION			
Project Number/N	ame:	3034.01 Ferndale Mo	otors		Well Number	r: MW-8	
Project Location:	524 Main St Ferndale, C		Casing Diameter: 1"		Well Depth f	rom TOC (BP): rom TOC (AP):	18.80
Date: September	r 23, 2005		Top of Screen:		Initial Well	Depth:	
Sampled by (print	and sign): Bria	n Hasik	Product Thickn	ess in inches:	7		
	ASE!		Water Level fro	om TOC:	68	Time:	2:05
Notes: Hand p Strong DU me	rge		Water Level pr	e-purge: 5. 6	9	Time:	19
Strong	He oder		Well Type:	Monitor □ Ext	raction 🗆 Oth		
DO me	les word !	Fit	Well EL (TOC)			ell Mat: PVC	
			WEATH	ER			
Wind: Yes No Rain: Yes No	Cloud Fog:	s: Yes/No	Sun	Yes No	Precipitation	in last 5 days: Y	Yes No
	VC	LUME OF WA	TER TO BE REM	OVER BEFOR	E SAMPLING		
(TD) 11.11		Dia. Inches	0.0408 = 6.4 s (Approx. 0.6 gal	1	one well volum	e ons purged	
		FIELD M	EASUREMENTS	DURING PUR	GING		
Stable Fiel	ld Parameters	Required Prior	to Sample Collect	ion <10% pH a	nd EC change, <	<0.2°C temp. cha	nge
Time	Gallons	РН	TEMP °C	ORP	DO mg/L	EC mS/μS	Turbidity H/M/L
1:25	0-5	6.69	17-9	-105		1259	M
1:31	j	6.59	17-0	- 99		1320	M
1:37	1.5	6.59	16-6	-74		1409	is
1742	2	6.49	1-6-5	-64		1386	M.
		`			^		
			**		NA		
Minimum of	f 5 gallons or 0	6 gal/ft Of wat	er in casing - whic	hover is greater		li	
Water Level Before			or in casing - will		Time: 45)		ible.
Appearance of Samp	le:					<u>U</u>	
Bailer: Disposable	Pun	np: 12V Subme	rsible (1-2 gpm)				
DECON. METHOD:				ble Rinse			
NUMBER OF DRUM			7 Soil:		ner:		
							





Alpha Analytical Laboratories Inc.

208 Mason St. Ukiah, California 95482

e-mail: clientservices@alpha-labs.com • Phone: (707) 468-0401 • Fax: (707) 468-5267

05 August 2005

Trans Tech Consultants

Attn: Bill Wiggins

930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492

RE: Tipple Motors

Work Order: A507529

Enclosed are the results of analyses for samples received by the laboratory on 07/22/05 14:35. If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Nena M. Burgess For Sheri L. Speaks

Project Manager



e-mail: clientservices@alpha-labs.com • Phone: (707) 468-0401 • Fax: (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 1 of 12

Trans Tech Consultants

930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492 Attn: Bill Wiggins

Report Date: 08/05/05 08:42

Project No: 3034.01

Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code

Client PO/Reference

A507529

07/22/2005 14:35

TRANSTEC

ANALYTICAL REPORT FOR SAMPLES

Sample ID	Laboratory ID	Matrix	Date Sampled	Date Received
MW-8-5	A507529-01	Soil	07/19/05 14:10	07/22/05 14:35
MW-8-14.5	A507529-02	Soil	07/19/05 14:15	07/22/05 14:35



e-mail clientservices@alpha labs.com • Phone (707) 468-0401 • Fax (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 2 of 12

Trans Tech Consultants 930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492 Attn: Bill Wiggins

Report Date: 08/05/05 08:42

Project No: 3034.01

Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code

Client PO/Reference

A507529

07/22/2005 14:35

TRANSTEC

	22/2003 14.33			MISTEC				
		Alpha A	nalytical	Laborato	ries, Inc.			
	METHOD	BATCH	PREPARED	ANALYZED	DILUTION	RESULT	PQL	NOTE
MW-8-5 (A507529-01)			Sample Ty	pe: Soil		Sampled: 07/19/05 14:10)	
TPH by EPA/LUFT GC/GCMS Metho	ods							
TPH as Diesel	8015DRO	AG52911	07/29/05	07/30/05	10	580 mg/kg	10	D-06
TPH as Gasoline	8015GRO	AG52813	07/22/05	07/27/05	500	3000 "	500	
Surrogate: 1,4-Bromofluorobenzene	8015DRO	AG52911	07/29/05	07/30/05		359 % 20	0-152	S-06
Surrogate: 1,4-Bromofluorobenzene	8015GRO	AG52813	07/22/05	07/27/05			0-156	2 00
Volatile Organic Compounds by EPA	Method 8260B							R-06
Benzene	EPA 8260B	AG52606	07/22/05	07/24/05	3464	ND mg/kg	17	
Toluene	II .	n	"	H .	n	ND"	17	
Ethylbenzene	**	11	ય	ŧr	n	ND"	17	
Xylenes (total)	н	n	"	н	**	ND "	17	
Methyl tert-butyl ether	**	11	**	n	11	ND "	17	
Di-isopropyl ether	**	11	11	tr	11	ND "	17	
Ethyl tert-butyl ether	**	n	**	11	11	ND "	17	
Tert-amyl methyl ether	**	n	**	n	**	ND"	17	
Tert-butyl alcohol	11	*1	"	11	e	ND"	350	
1,2-Dichloroethane	11	11		11	II.	ND"	17	
Chlorobenzene	"	н	**	н	n	ND "	17	
1,3-Dichlorobenzene	11	n	**	n	n	ND"	17	
1,4-Dichlorobenzene	Ħ	**	•	n	n	ND"	17	
1,2-Dichlorobenzene	"	"	"	**	11	ND "	17	A6
1,2-Dibromoethane (EDB)	Ħ	11	11	**	*1	ND "	17	
Surrogate: Bromofluorobenzene	"	"	"	"		121 % 64	4-151	
Surrogate: Dibromofluoromethane	"	"	"	"			8-133	
Surrogate: Toluene-d8	"	"	"	"		101 % 89	9-148	
MW-8-14.5 (A507529-02)			Sample Ty	pe: Soil		Sampled: 07/19/05 14:15	;	
TPH by EPA/LUFT GC/GCMS Metho	ods							
TPH as Diesel	8015DRO	AG52911	07/29/05	07/30/05	1	5.7 mg/kg	1.0	
TPH as Gasoline	5035/8015GRO	AH50111	07/19/05	07/30/05	11	5,9 "	1.0	
Surrogate: 1,4-Bromofluorobenzene	"	"	11	"		105 % 66	0-156	
Surrogate: 1,4-Bromofluorobenzene	8015DRO	AG52911	07/29/05	07/30/05			0-152	



Alpha Analytical Laboratories Inc.

208 Mason St. Ukiah, California 95482

e-mail: clientservices@alpha-labs.com • Phone: (707) 468-0401 • Fax: (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 3 of 12

Trans Tech Consultants

930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492 Attn: Bill Wiggins

Report Date: 08/05/05 08:42

Project No: 3034.01

Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code

Client PO/Reference

A507529

07/22/2005 14:35

TRANSTEC

		Alpha A	nalytical	Laborator	ries, Inc.			
	METHOD	BATCH	PREPARED	ANALYZED	DILUTION	RESULT	PQL	NOTE
MW-8-14.5 (A507529-02)			Sample Ty	e: Soil	Sa	mpled: 07/19/05 14:	15	
Volatile Organic Compounds by EPA	Methods 8260B/	5035						
Benzene	EPA 8260B	AG52520	07/19/05	07/23/05	1	ND mg/kg	0.0050	
Toluene	"	ıı	11	11	11	ND "	0.0050	
Ethylbenzene	**	н	11	**	0	ND "	0.0050	
Xylenes (total)	**	Ħ	10	#	n	ND "	0.0050	
Methyl tert-butyl ether	**	n	17	n	19	ND "	0.0050	
Di-isopropyl ether	"	H	19	07/24/05	n	0.65 "	0.0050	
Ethyl tert-butyl ether	**	н	19	07/23/05	11	ND "	0.0050	
Tert-amyl methyl ether	11	H	n	ii.	n	ND "	0.0050	
Tert-butyl alcohol	19	**	17	11	n	ND "	0.10	
1,2-Dichloroethane	"	**	11	10	11	0.028 "	0.0050	
Chlorobenzene	11	*1	n	17	"	ND "	0.0050	
1,3-Dichlorobenzene	n	n	n	н	**	ND "	0.0050	
1,4-Dichlorobenzene	ıı	rt .	н	II	Ħ	ND "	0.0050	
1,2-Dichlorobenzene	Ħ	11	**	н	"	ND "	0.0050	
1,2-Dibromoethane (EDB)	п	n	**	n	**	ND "	0.0050	
Surrogate: Bromofluorobenzene	"	"	"	"		106 %	74-138	
Surrogate: Dibromofluoromethane	"	"	n	"		95.9 %	75-137	
Surrogate: Toluene-d8	"	"	**	"		111 %	88-142	



e-mail: clientservices@alpha-labs.com • Phone: (707) 468-0401 • Fax: (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 4 of 12

Trans Tech Consultants 930 Shiloh Rd., Bldg.44, Suite J Windsor, CA 95492

Attn: Bill Wiggins

Report Date: 08/05/05 08:42

Project No: 3034.01

Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code TRANSTEC Client PO/Reference

A507529

07/22/2005 14:35

TPH by EPA/LUFT GC/GCMS Methods - Quality Control

Analyte(s)	Result	PQL	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Flag
Batch AG52813 - EPA 5035 GC										
Blank (AG52813-BLK1)				Prepared	& Analyze	d: 07/27/	05			
TPH as Gasoline	ND	1.0	mg/kg					***		
Surrogate: 1,4-Bromofluorobenzene	3.69		"	4.00		92.2	60-156			
LCS (AG52813-BS1)				Prepared & Analyzed: 07/27/05						
TPH as Gasoline	19.1	1.0	mg/kg	24.0		79.6	77-139			
Surrogate: 1,4-Bromofluorobenzene	3.59		"	4.00		89.8	60-156			
Matrix Spike (AG52813-MS1)	Sou	rce: A507	Prepared	& Analyze						
TPH as Gasoline	19.3	1.0	mg/kg	24.0	ND	80.4	72-138			
Surrogate: 1,4-Bromofluorobenzene	3.94		11	4.00		98.5	60-156			
Matrix Spike Dup (AG52813-MSD1)	Sou	rce: A507	500-01	Prepared	& Analyze	d: 07/27/	05			
TPH as Gasoline	17.1	1.0	mg/kg	24.0	ND	71.2	72-138	12.1	25	QM-07
Surrogate: 1,4-Bromofluorobenzene	3.80		11	4.00		95.0	60-156			
Batch AG52911 - CA LUFT - orb shake	r									(6 ₁)
Blank (AG52911-BLK1)				Prepared	& Analyze	d: 07/29/	05			
TPH as Diesel	ND	1.0	mg/kg							
Surrogate: 1,4-Bromofluorobenzene	5.18	to the second way	H	11.6		44.7	20-152			 -
LCS (AG52911-BS1)				Prepared	& Analyze	ed: 07/29/	05			
TPH as Diesel	44.0	1.0	mg/kg	39.2		112	63-126			
C 1 / D / /	6.82		11	11.6		58.8	20-152			
Surrogaie: 1,4-Bromojiuorovenzene										
Surrogate: 1,4-Bromofluorobenzene Matrix Spike (AG52911-MS1)		rce: A507	′593-01	Prepared	& Analyze	ed: 07/29/	05			



e-mail: clientservices@alpha-labs.com • Phone: (707) 468-0401 • Fax: (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 5 of 12

Trans Tech Consultants

930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492 Attn: Bill Wiggins

Report Date: 08/05/05 08:42

Project No: 3034.01

Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code

Client PO/Reference

A507529

07/22/2005 14:35

TRANSTEC

TPH by EPA/LUFT GC/GCMS Methods - Quality Control

	-				_	•				
Analyte(s)	Result	PQL	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Flag
Batch AG52911 - CA LUFT - orb sha	aker									
Matrix Spike (AG52911-MS1)	Sou	rce: A507	593-01	Prepared	& Analyzo	ed: 07/29/	05			
Surrogate: 1,4-Bromofluorobenzene	6.64		#	11.6		57.2	20-152			
Matrix Spike Dup (AG52911-MSD1)	Sou	Source: A507593-01 P			: 07/29/05	Analyzed	l: 07/30/05			
TPH as Diesel	42.6	1.0	mg/kg	39.2	ND	109	61-134	8.54	20	
Surrogate: 1,4-Bromofluorobenzene	5.72		"	11.6		49.3	20-152		<u> </u>	
Batch AH50111 - EPA 5035 GC										
Blank (AH50111-BLK1)				Prepared	& Analyzo	ed: 07/30/	05			
TPH as Gasoline	ND	1.0	mg/kg							
Surrogate: 1,4-Bromofluorobenzene	3.98		"	4.00		99.5	60-156			
LCS (AH50111-BS1)				Prepared	& Analyzo	ed: 07/30/	05			
TPH as Gasoline	20.3	1.0	mg/kg	24.0		84.6	77-139			
Surrogate: 1,4-Bromofluorobenzene	4.18		"	4.00		104	60-156			
LCS Dup (AH50111-BSD1)				Prepared	& Analyzo	ed: 07/30/	05			
TPH as Gasoline	22.4	1.0	mg/kg	24.0		93.3	77-139	9.84	20	el.
Surrogate: 1,4-Bromofluorobenzene	3.88		11	4.00		97.0	60-156			



e-mail: clientservices@alpha-labs.com * Phone: (707) 468-0401 * Fax: (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 6 of 12

Trans Tech Consultants 930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492 Attn: Bill Wiggins

Report Date: 08/05/05 08:42

Project No: 3034.01 Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code

Client PO/Reference

A507529

07/22/2005 14:35

TRANSTEC

Volatile Organic Compounds by EPA Method 8260B - Quality Control

Analyte(s)	Result	PQL	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Flag
Batch AG52606 - EPA 5035 GCMS			·							
Blank (AG52606-BLK1)				Prepared	& Analyze	ed: 07/23/	05			R-11
Benzene	ND	0.87	mg/kg	······						
Toluene	ND	0.87	11							
Ethylbenzene	ND	0.87	H							
Xylenes (total)	ND	0.87	"							
Methyl tert-butyl ether	ND	0.87	H							
Di-isopropyl ether	ND	0.87	n							
Ethyl tert-butyl ether	ND	0.87	n							
Tert-amyl methyl ether	ND	0.87	Ħ							
Tert-butyl alcohol	ND	17	*							
1,2-Dichloroethane	ND	0.87	n							
Chlorobenzene	ND	0.87	*1							
1,3-Dichlorobenzene	ND	0.87	**							
1,4-Dichlorobenzene	ND	0.87	**							
1,2-Dichlorobenzene	ND	0.87	**							
1,2-Dibromoethane (EDB)	ND	0.87	11							
Surrogate: Bromofluorobenzene	5.21		n	4.33		120	64-151		**	4 .
Surrogate: Dibromofluoromethane	3.61		n	4.33		83.4	68-133			-
Surrogate: Toluene-d8	4.52		и	4.33		104	89-148			
LCS (AG52606-BS1)				Prepared	& Analyze	ed: 07/23/	05			
Benzene	1.75	0.87	mg/kg	1.73		101	72-123			
Toluene	1.81	0.87	"	1.73		105	72-126			
Ethylbenzene	1.81	0.87	"	1.73		105	71-125			
Xylenes (total)	5.25	0.87	**	5.19		101	67-127			
Methyl tert-butyl ether	1.83	0.87		1.73		106	71-127			
Di-isopropyl ether	1.84	0.87	**	1.75		105	62-99			QL-03
Ethyl tert-butyl ether	1.86	0.87	"	1.76		106	56-140			

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

Nena M. Burgess For Sheri L. Speaks Project Manager

8/5/2005



e-mall: clientservices@alpha-labs.com • Phone: (707) 468-0401 • Fax: (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 7 of 12

Trans Tech Consultants

930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492 Attn: Bill Wiggins

Report Date: 08/05/05 08:42

Project No: 3034.01

Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code

Client PO/Reference

A507529

07/22/2005 14:35

TRANSTEC

Volatile Organic Compounds by EPA Method 8260B - Quality Control

Analyte(s)	Result	PQL	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Flag
Batch AG52606 - EPA 5035 GCMS										
LCS (AG52606-BS1)				Prepared	& Analyze	d: 07/23/0	05			
Tert-amyl methyl ether	1.79	0.87	11	1.79		100	66-129			
Tert-butyl alcohol	30.9	17	n	34.0		90.9	42-124			
1,2-Dichloroethane	1.68	0.87	n.	1.73		97.1	69-125			
Chlorobenzene	1.80	0.87	н	1.73		104	76-117			
1,3-Dichlorobenzene	1.73	0.87	n	1.73		100	71-125			
1,4-Dichlorobenzene	1.83	0.87	*1	1.73		106	81-117			
1,2-Dichlorobenzene	1.80	0.87	11	1.73		104	82-115			
1,2-Dibromoethane (EDB)	1.98	0.87	**	1.73		114	71-131			
Surrogate: Bromofluorobenzene	4.89		"	4.33		113	64-151			
Surrogate: Dibromofluoromethane	3.45		"	4.33		79.7	68-133			
Surrogate: Toluene-d8	4.07		"	4.33		94.0	89~148			
LCS Dup (AG52606-BSD1)				Prepared	: 07/23/05	Analyzed	07/24/05			
Benzene	1.76	0.87	mg/kg	1.73		102	72-123	0.570	25	
Toluene	1.84	0.87	"	1.73		106	72-126	1.64	25	
Ethylbenzene	1.88	0.87	11	1.73		109	71-125	3.79	25	
Xylenes (total)	5.52	0.87	*	5.19		106	67-127	5.01	25	20
Methyl tert-butyl ether	1.74	0.87	н	1.73		101	71-127	5.04	25	
Di-isopropyl ether	1.81	0.87	н	1.75		103	62-99	1.64	25	QL-03
Ethyl tert-butyl ether	1.81	0.87	**	1.76		103	56-140	2.72	25	,
Tert-amyl methyl ether	1.74	0.87	Ŧf	1.79		97.2	66-129	2.83	25	
Tert-butyl alcohol	36.8	17	39	34.0		108	42-124	17.4	25	
1,2-Dichloroethane	1.74	0.87	ft	1.73		101	69-125	3.51	25	
Chlorobenzene	1.85	0.87	31*	1.73		107	76-117	2.74	25	
1,3-Dichlorobenzene	1.84	0.87	19	1.73		106	71-125	6.16	25	
1,4-Dichlorobenzene	1.83	0.87	"	1.73		106	81-117	0.00	25	
1,2-Dichlorobenzene	1.81	0.87	"	1.73		105	82-115	0.554	25	



Alpha √Analytical Laboratories Inc.

208 Mason St. Ukiah, California 95482

e-mail: clientservices@alpha-labs.com • Phone: (707) 468-0401 • Fax: (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 8 of 12

Trans Tech Consultants

930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492 Attn: Bill Wiggins

Report Date: 08/05/05 08:42

Project No: 3034.01

Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code

Client PO/Reference

A507529

07/22/2005 14:35

TRANSTEC

Volatile Organic Compounds by EPA Method 8260B - Quality Control

Analyte(s)	Result	PQL	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Flag
Batch AG52606 - EPA 5035 GCMS									· · · · ·	
LCS Dup (AG52606-BSD1)				Prepared	07/23/05	Analyzed	: 07/24/05			
1,2-Dibromoethane (EDB)	1.89	0.87	ıı	1.73		109	71-131	4.65	25	
Surrogate: Bromofluorobenzene	5.15		,,	4.33	,	119	64-151			
Surrogate: Dibromofluoromethane	3.72		н	4.33		85.9	68-133			
Surrogate: Toluene-d8	4.13		"	4.33		95.4	89-148			
Matrix Spike (AG52606-MS1)	Sou	rce: A507	516-04	Prepared	: 07/23/05	Analyzed	: 07/24/05			
Benzene	2.36	0.87	mg/kg	1.73	ND	136	49-137			
Toluene	2.42	0.87	Ħ	1.73	ND	140	50-148			
Ethylbenzene	3.00	0.87	**	1.73	ND	136	55-138			
Xylenes (total)	7.23	0.87	Ħ	5.19	ND	137	54-139			
Methyl tert-butyl ether	2.29	0.87	n	1.73	ND	132	50-140			
Di-isopropyl ether	2.49	0.87	n	1.75	ND	142	48-117			QM-05
Ethyl tert-butyl ether	2.48	0.87	н	1.76	ND	141	33-156			-
Tert-amyl methyl ether	2.36	0.87	**	1.79	ND	132	37-153			
Tert-butyl alcohol	45.7	17	11	34.0	ND	134	48-127			QM-05
1,2-Dichloroethane	2.13	0.87	**	1.73	ND	123	47-149			
Chlorobenzene	2.35	0.87	**	1.73	ND	136	54-133			QM-05
1,3-Dichlorobenzene	2.28	0.87	11	1.73	ND	132	17-157			•
1,4-Dichlorobenzene	2.30	0.87		1.73	ND	133	30-150			
1,2-Dichlorobenzene	2.28	0.87	"	1.73	ND	132	28-150			
1,2-Dibromoethane (EDB)	2.50	0.87	II.	1.73	ND	145	35-156			
Surrogate: Bromofluorobenzene	4.83		"	4.33		112	64-151			
Surrogate: Dibromofluoromethane	3.32		"	4.33		76.7	68-133			
Surrogate: Toluene-d8	3.97		"	4.33		91.7	89-148			



e-mail: clientservices@alpha-labs.com • Phone: (707) 468-0401 • Fax: (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 9 of 12

Trans Tech Consultants

930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492 Attn: Bill Wiggins Report Date: 08/05/05 08:42

Project No: 3034.01

Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code

Client PO/Reference

A507529

07/22/2005 14:35

TRANSTEC

Volatile Organic Compounds by EPA Methods 8260B/5035 - Quality Control

Analyte(s)	Result	PQL	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Flag
Batch AG52520 - EPA 5035 GCMS										
Blank (AG52520-BLK1)				Prepared:	07/21/05	Analyzed	: 07/22/05			
Benzene	ND	0.0050	mg/kg	***************************************		.				
Toluene	ND	0.0050	**							
Ethylbenzene	ND	0.0050	**							
Xylenes (total)	ND	0.0050	**							
Methyl tert-butyl ether	ND	0.0050	#							
Di-isopropyl ether	ND	0.0050	**							
Ethyl tert-butyl ether	ND	0.0050	31							
Tert-amyl methyl ether	ND	0.0050	II.							
Tert-butyl alcohol	ND	0.10	"							
1,2-Dichloroethane	ND	0.0050	**							
Chlorobenzene	ND	0.0050	11							
1,3-Dichlorobenzene	ND	0.0050	n							
1,4-Dichlorobenzene	ND	0.0050	н							
1,2-Dichlorobenzene	ND	0.0050	**							
1,2-Dibromoethane (EDB)	ND	0.0050	"							
Surrogate: Bromofluorobenzene	0.0260		"	0.0250		104	74-138			4
Surrogate: Dibromofluoromethane	0.0285		n	0.0250		114	75-137			
Surrogate: Toluene-d8	0.0296		n	0.0250		118	88-142			
LCS (AG52520-BS1)				Prepared:	07/21/05	Analyzed	: 07/22/05			
Benzene	0.00512	0.0050	mg/kg	0.00500		102	72-123			
Toluene	0.00565	0.0050	n	0.00500		113	72-126			
Ethylbenzene	0.00506	0.0050	17	0.00500		101	71-125			
Xylenes (total)	0.0155	0.0050	e e	0.0150		103	67-127			
Methyl tert-butyl ether	0.00598	0.0050	19	0.00500		120	71-127			
Di-isopropyl ether	0.00539	0.0050	"	0.00507		106	62-99			QL-0
Ethyl tert-butyl ether	0.00541	0.0050	"	0.00508		106	56-140			•

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

123-

Nena M. Burgess For Sheri L. Speaks Project Manager

8/5/2005



Alpha Analytical Laboratories Inc.

208 Mason St. Ukiah, California 95482

e-mail: clientservices@alpha-labs.com • Phone: (707) 468-0401 • Fax: (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 10 of 12

Trans Tech Consultants 930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492 Attn: Bill Wiggins

Report Date: 08/05/05 08:42

Project No: 3034.01 Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code

Client PO/Reference

A507529

07/22/2005 14:35

TRANSTEC

Volatile Organic Compounds by EPA Methods 8260B/5035 - Quality Control

Analyte(s)	Result	PQL	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Flag
Batch AG52520 - EPA 5035 GCMS										
LCS (AG52520-BS1)				Prepared:	07/21/05	Analyzed	: 07/22/05			
Tert-amyl methyl ether	0.00495	0.0050	н	0.00516		95.9	66-129			
Tert-butyl alcohol	0.0989	0.10	н	0.0982		101	42-124			
1,2-Dichloroethane	0.00530	0.0050	Ħ	0.00500		106	64-117			
Chlorobenzene	0.00530	0.0050	Ħ	0.00500		106	76-117			
1,3-Dichlorobenzene	0.00517	0.0050	Ħ	0.00500		103	65-124			
1,4-Dichlorobenzene	0.00527	0.0050	**	0.00500		105	71-120			
1,2-Dichlorobenzene	0.00522	0.0050	"	0.00500		104	70-121			
1,2-Dibromoethane (EDB)	0.00524	0.0050	11	0.00500		105	70-132			
Surrogate: Bromofluorobenzene	0.0264		"	0.0250		106	74-138			
Surrogate: Dibromofluoromethane	0.0256		n	0.0250		102	75-137			
Surrogate: Toluene-d8	0.0272		"	0.0250		109	88-142			
LCS Dup (AG52520-BSD1)				Prepared:	07/21/05	Analyzed	: 07/22/05			
Benzene	0.00520	0.0050	mg/kg	0.00500		104	72-123	1.55	25	
Toluene	0.00563	0.0050	n	0.00500		113	72-126	0.355	25	
Ethylbenzene	0.00505	0.0050	Ħ	0.00500		101	71-125	0.198	25	
Xylenes (total)	0.0155	0.0050	"	0.0150		103	67-127	0.00	25	120
Methyl tert-butyl ether	0.00611	0.0050	**	0.00500		122	71-127	2.15	25	
Di-isopropyl ether	0.00558	0.0050	**	0.00507		110	62-99	3.46	25	QL-03
Ethyl tert-butyl ether	0.00553	0.0050	11	0.00508		109	56-140	2.19	25	
Tert-amyl methyl ether	0.00522	0.0050	11	0.00516		101	66-129	5.31	25	
Tert-butyl alcohol	0.105	0.10	"	0.0982		107	42-124	5.98	25	
1,2-Dichloroethane	0.00540	0.0050	н	0.00500		108	64-117	1.87	25	
Chlorobenzene	0.00534	0.0050	n	0.00500		107	76-117	0.752	25	
1,3-Dichlorobenzene	0.00526	0.0050	п	0.00500		105	65-124	1.73	25	
1,4-Dichlorobenzene	0.00525	0.0050	**	0.00500		105	71-120	0.380	25	
1,2-Dichlorobenzene	0.00521	0.0050	11	0.00500		104	70-121	0.192	25	



rtical Laboratories Inc. 208 Mason St. Ukiah, California 95482

e-mail: clientservices@alpha-labs.com • Phone: (707) 468-0401 • Fax: (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 11 of 12

Trans Tech Consultants 930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492 Attn: Bill Wiggins Report Date: 08/05/05 08:42

Project No: 3034.01 Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code

Client PO/Reference

A507529

07/22/2005 14:35

TRANSTEC

Volatile Organic Compounds by EPA Methods 8260B/5035 - Quality Control

Analyte(s)	Result	PQL	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Flag
Batch AG52520 - EPA 5035 GCMS										·
LCS Dup (AG52520-BSD1)				Prepared:	07/21/05	Analyzed	: 07/22/05			
1,2-Dibromoethane (EDB)	0.00551	0.0050	n	0.00500		110	70-132	5.02	25	
Surrogate: Bromofluorobenzene	0.0266		n	0.0250		106	74-138			***************************************
Surrogate: Dibromofluoromethane	0.0260		**	0.0250		104	75-137			
Surrogate: Toluene-d8	0.0272		"	0.0250		109	88-142			
Matrix Spike (AG52520-MS1)	Sou	urce: A507	500-01	Prepared:	07/21/05	Analyzed	: 07/22/05			
Benzene	0.00565	0.0050	mg/kg	0.00500	ND	113	49-137			
Γoluene	0.00584	0.0050		0.00500	ND	117	50-148			
Ethylbenzene	0.00456	0.0050	"	0.00500	ND	91.2	55-138			
Xylenes (total)	0.0138	0.0050	Ħ	0.0150	ND	92.0	54-139			
Methyl tert-butyl ether	0.00673	0.0050	**	0.00500	ND	103	50-140			
Di-isopropyl ether	0.00543	0.0050	**	0.00507	ND	107	48-117			
Ethyl tert-butyl ether	0.00538	0.0050		0.00508	ND	106	33-156			
Tert-amyl methyl ether	0.00504	0.0050	"	0.00516	ND	97.7	37-153			
Tert-butyl alcohol	0.0969	0.10	**	0.0982	ND	98.7	48-127			
1,2-Dichloroethane	0.00508	0.0050	11	0.00500	ND	102	55-125			
Chlorobenzene	0.00485	0.0050		0.00500	ND	97.0	54-133			施
1,3-Dichlorobenzene	0.00389	0.0050	H	0.00500	ND	77.8	45-138			
1,4-Dichlorobenzene	0.00473	0.0050	н	0.00500	ND	94.6	60-136			
1,2-Dichlorobenzene	0.00465	0.0050	"	0.00500	ND	93.0	36-156			
1,2-Dibromoethane (EDB)	0.00510	0.0050	Ħ	0.00500	ND	102	36-156			
Surrogate: Bromofluorobenzene	0.0251		"	0.0250		100	74-138	·····	TOTAL VALUE OF THE PARTY OF THE	
Surrogate: Dibromofluoromethane	0.0256		"	0.0250		102	75-137			
Surrogate: Toluene-d8	0.0276		"	0.0250		110	88-142			

The results in this report apply to the samples analyzed in accordance with the chain of custody document. This analytical report must be reproduced in its entirety.

123-



e-mail: clientservices@alpha labs.com • Phone: (707) 468-0401 • Fax: (707) 468-5267

CHEMICAL EXAMINATION REPORT

Page 12 of 12

Trans Tech Consultants

930 Shiloh Rd., Bldg.44, Suite J

Windsor, CA 95492 Attn: Bill Wiggins

Project No: 3034.01

Report Date: 08/05/05 08:42

Project ID: Tipple Motors

Order Number

Receipt Date/Time

Client Code

Client PO/Reference

A507529

07/22/2005 14:35

TRANSTEC

Notes and Definitions

S-06	The recovery of this surrogate is outside control limits due to sample dilution required from high analyte
	concentration and/or matrix interferences.

R-11 All samples and QC in the batch were analyzed to meet high-level reporting limits.

R-06 The Reporting Limits for this analysis have been raised to account for matrix interference.

OM-07 The spike recovery was outside acceptance limits for the MS and/or MSD. The batch was accepted based on acceptable LCS recovery.

QM-05 The spike recovery was outside acceptance limits for the MS and/or MSD due to matrix interference. The LCS and/or LCSD were within acceptance limits showing that the laboratory is in control and the data is acceptable.

QL-03 Although the LCS/LCSD recovery for this analyte is outside of in-house developed control limits, it is within the EPA recommended range of 70-130%.

D-06 The sample chromatographic pattern does not resemble the fuel standard used for quantitation.

DET Analyte DETECTED

Analyte NOT DETECTED at or above the reporting limit

NR Not Reported

ND

Sample results reported on a dry weight basis dry


RPD Relative Percent Difference

PQL Practical Quantitation Limit

WORK ORDER CHAIN OF CUSTODY RECORD

Alpha ¹ Analytical Laboratories Inc. • 208 Mason Street, Ukiah, CA 95482 • (707) 468-0401 • FAX (707) 468-5267

HAZARDOUS MATERIALS ARE THE PROPERTY OF THE CLIENT. THE CLIENT IS RESPONSIBLE FOR PROPER DISPOSAL OF HAZARDOUS WASTES, CLIENTS NOT PICKING UP HAZARDOUS WASTES MAY BE ASSESSED AN APPROPRIATE FEE. 1. STORAGE TIME REQUESTED ______ DAYS (SAMPLES WILL BE STORED FOR 30 DAYS WITHOUT ADDITIONAL CHARGES: THEREAFTER STORAGE CHARGES WILL BE BILLED AT THE PUBLISHED RATES.) SAMPLE CONDITION ON RECEIPT: EXPLAIN IRREGULARITIES BELOW TURN AROUND TIME REQUESTED 70003500046 19/05 PAGE. WERE SAMPLES PRESERVED? 2 _ BUBBLES OR AIR SPACE? ☐ YES STANDARD COLD/ICED? Geota Mete 2. SAMPLE TO BE RETURNED TO CLIENT? ANALYSES SAMPLE CONTROL OFFICEF SAMPLE DESPOSITION: 1820 724-05 DATE 公司 Mind in 132 PROJECT MANAGER TOTAL TIME PHONE NUMBER 200 SITE CONTACT FAX NUMBER LAB SAMPLE NUMBER SAMPLED BY 김 1435 (SIGNATURE)
RECEIVED FOR
LABORATORY BY: AUTHORIZED BY: (SIGNATURE) RECEIVED BY RECEIVED BY 30.4.0 7:10 TIME 3/10 4/19 DATE SITE TIME 2 (A) 2 CONTRACT/PURCHASE ORDER/QUOTE NUMBER SAMPLE NUMBER/IDENTIFICATION SIGNATURE OF PERSON AUTHORIZING WORK UNDER TERMS STATED ON REVERSE SIDE OF 4. 2018 CLIENT'S NAME STRCK d MAC 1 00 PECIAL INSTRUCTIONS METHOD OF SHIPMENT RELINQUISHED BY: STREET ADDRESS RELINQUISHED BY RELINQUISHED B PROJECT NAME (SIGNATURE) DRIVING TIME (SIGNATURE) (SIGNATURE)





Report Number: 46153

Date: 10/03/2005

Brian Hasik Trans Tech Consultants 930 Shiloh Rd., Building 44, Suite J Windsor, CA 95492

Subject: 8 Water Samples and 1 Vapor Sample

Project Name : Tipple Motors Project Number : 3034.01

Dear Mr. Hasik,

Chemical analysis of the samples referenced above has been completed. Summaries of the data are contained on the following pages. Sample(s) were received under documented chain-of-custody. US EPA protocols for sample storage and preservation were followed.

Kiff Analytical is certified by the State of California (# 2236). If you have any questions regarding procedures or results, please call me at 530-297-4800.

Sincerely,



Report Number: 46153

Date: 10/03/2005

Subject :

8 Water Samples and 1 Vapor Sample

Project Name :

Tipple Motors

Project Number :

3034.01

Case Narrative

Matrix Spike/Matrix Spike Duplicate Results associated with sample MW-1 for the analyte Tert-Butanol were affected by the analyte concentrations already present in the un-spiked sample.

The Method Reporting Limit for TPH as Diesel is increased due to interference from Gasoline-Range Hydrocarbons for samples MW-2 and MW-8.

Approved By:

Joe Kiff

2795 2nd St, Suite 300 Davis, CA 95616 530-297-4800



Project Name : **Tipple Motors**

Project Number: 3034.01

Sample: MW-1

Sample Date :09/22/2005

Matrix: Water

Lab Number : 46153-01

Report Number: 46153 Date: 10/03/2005

		Method			
Parameter	Measured Value	Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Methyl-t-butyl ether (MTBE)	44	0.50	ug/L	EPA 8260B	09/30/2005
Diisopropyl ether (DIPE)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Tert-amyl methyl ether (TAME)	16	0.50	ug/L	EPA 8260B	09/30/2005
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	09/30/2005
TPH as Gasoline	54	50	ug/L	EPA 8260B	09/30/2005
1,2-Dichloroethane	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
1,2-Dibromoethane	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Toluene - d8 (Surr)	96.3		% Recovery	EPA 8260B	09/30/2005
4-Bromofluorobenzene (Surr)	107		% Recovery	EPA 8260B	09/30/2005
Dibromofluoromethane (Surr)	99.9		% Recovery	EPA 8260B	09/30/2005
1,2-Dichloroethane-d4 (Surr)	97.0		% Recovery	EPA 8260B	09/30/2005
TPH as Diesel	< 50	50	ug/L	M EPA 8015	09/29/2005
Octacosane (Diesel Surrogate)	102		% Recovery	M EPA 8015	09/29/2005

Approved By:



Project Name : **Tipple Motors**

Project Number: 3034.01

Sample: MW-2

Sample Date :09/22/2005

Report Number: 46153

Date: 10/03/2005

Matrix: Water

Lab Number: 46153-02

Cample Date .09/22/2003					
Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	1500	3.0	ug/L	EPA 8260B	10/01/2005
Toluene	14	3.0	ug/L	EPA 8260B	10/01/2005
Ethylbenzene	52	3.0	ug/L	EPA 8260B	10/01/2005
Total Xylenes	23	3.0	ug/L	EPA 8260B	10/01/2005
Methyl-t-butyl ether (MTBE)	16	3.0	ug/L	EPA 8260B	10/01/2005
Diisopropyl ether (DIPE)	65	3.0	ug/L	EPA 8260B	10/01/2005
Ethyl-t-butyl ether (ETBE)	< 3.0	3.0	ug/L	EPA 8260B	10/01/2005
Tert-amyl methyl ether (TAME)	< 3.0	3.0	ug/L	EPA 8260B	10/01/2005
Tert-Butanol	< 15	15	ug/L	EPA 8260B	10/01/2005
TPH as Gasoline	6500	300	ug/L	EPA 8260B	10/01/2005
1,2-Dichloroethane	23	5.0	ug/L	EPA 8260B	09/30/2005
1,2-Dibromoethane	< 5.0	5.0	ug/L	EPA 8260B	09/30/2005
Toluene - d8 (Surr)	90.7		% Recovery	EPA 8260B	10/01/2005
4-Bromofluorobenzene (Surr)	102		% Recovery	EPA 8260B	10/01/2005
Dibromofluoromethane (Surr)	108		% Recovery	EPA 8260B	09/30/2005
1,2-Dichloroethane-d4 (Surr)	98.5		% Recovery	EPA 8260B	09/30/2005
TPH as Diesel	< 1000	1000	ug/L	M EPA 8015	09/29/2005
Octacosane (Diesel Surrogate)	105		% Recovery	M EPA 8015	09/29/2005

Approved By:



Project Name: **Tipple Motors**

Project Number: 3034.01

Sample Date :09/22/2005

Sample: MW-3

Matrix: Water

Lab Number: 46153-03

Report Number: 46153 Date: 10/03/2005

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	09/29/2005
Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/29/2005
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/29/2005
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/29/2005
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/29/2005
Diisopropyl ether (DIPE)	0.59	0.50	ug/L	EPA 8260B	09/29/2005
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	09/29/2005
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	09/29/2005
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	09/29/2005
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	09/29/2005
1,2-Dichloroethane	< 0.50	0.50	ug/L	EPA 8260B	09/29/2005
1,2-Dibromoethane	< 0.50	0.50	ug/L	EPA 8260B	09/29/2005
Toluene - d8 (Surr)	93.3		% Recovery	EPA 8260B	09/29/2005
4-Bromofluorobenzene (Surr)	104		% Recovery	EPA 8260B	09/29/2005
Dibromofluoromethane (Surr)	115		% Recovery	EPA 8260B	09/29/2005
1,2-Dichloroethane-d4 (Surr)	104		% Recovery	EPA 8260B	09/29/2005
TPH as Diesel	< 50	50	ug/L	M EPA 8015	09/29/2005
Octacosane (Diesel Surrogate)	98.6		% Recovery	M EPA 8015	09/29/2005

Approved By:



Project Name : **Tipple Motors**

Project Number: 3034.01

Sample: MW-4

Sample Date :09/22/2005

Report Number: 46153

Date: 10/03/2005

Matrix: Water

Lab Number : 46153-04

Sample Date .03/22/2005					
Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	6.6	0.50	ug/L	EPA 8260B	09/30/2005
Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Methyl-t-butyl ether (MTBE)	18	0.50	ug/L	EPA 8260B	09/30/2005
Diisopropyl ether (DIPE)	22	0.50	ug/L	EPA 8260B	09/30/2005
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	09/30/2005
TPH as Gasoline	170	50	ug/L	EPA 8260B	09/30/2005
1,2-Dichloroethane	0.60	0.50	ug/L	EPA 8260B	09/30/2005
1,2-Dibromoethane	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Toluene - d8 (Surr)	95.4		% Recovery	EPA 8260B	09/30/2005
4-Bromofluorobenzene (Surr)	103		% Recovery	EPA 8260B	09/30/2005
Dibromofluoromethane (Surr)	113		% Recovery	EPA 8260B	09/30/2005
1,2-Dichloroethane-d4 (Surr)	105		% Recovery	EPA 8260B	09/30/2005
TPH as Diesel	320	50	ug/L	M EPA 8015	09/29/2005
Octacosane (Diesel Surrogate)	105		% Recovery	M EPA 8015	09/29/2005

Approved By:



Project Name : **Tipple Motors**

Project Number: 3034.01

Sample: MW-5

Sample Date :09/22/2005

Matrix: Water

Lab Number: 46153-05

Report Number: 46153

Date: 10/03/2005

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date
Benzene	< 0.50	0.50	ug/L	EPA 8260B	Analyzed
Toluene	< 0.50	0.50	ug/L ug/L	EPA 8260B	09/30/2005
Ethylbenzene	< 0.50	0.50	ug/L ug/L	EPA 8260B	09/30/2005
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005 09/30/2005
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Diisopropyl ether (DIPE)	16	0.50	ug/L	EPA 8260B	09/30/2005
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	09/30/2005
TPH as Gasoline	110	50	ug/L , .	EPA 8260B	09/30/2005
1,2-Dichloroethane	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
1,2-Dibromoethane	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Toluene - d8 (Surr)	99.4		% Recovery	EPA 8260B	09/30/2005
4-Bromofluorobenzene (Surr)	101		% Recovery	EPA 8260B	09/30/2005
Dibromofluoromethane (Surr)	113		% Recovery	EPA 8260B	09/30/2005
1,2-Dichloroethane-d4 (Surr)	102		% Recovery	EPA 8260B	09/30/2005
TPH as Diesel	230	50	ug/L	M EPA 8015	09/29/2005
Octacosane (Diesel Surrogate)	110		% Recovery	M EPA 8015	09/29/2005

Approved By:



Project Name: **Tipple Motors**

Project Number: 3034.01

Sample: MW-6

Matrix: Water

Lab Number: 46153-06

Report Number: 46153

Date: 10/03/2005

Sample (Date	:09/22	/2005
----------	------	--------	-------

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Diisopropyl ether (DIPE)	3.6	0.50	ug/L	EPA 8260B	09/30/2005
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	09/30/2005
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	09/30/2005
1,2-Dichloroethane	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
1,2-Dibromoethane	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Toluene - d8 (Surr)	97.4		% Recovery	EPA 8260B	09/30/2005
4-Bromofluorobenzene (Surr)	102		% Recovery	EPA 8260B	09/30/2005
Dibromofluoromethane (Surr)	114		% Recovery	EPA 8260B	09/30/2005
1,2-Dichloroethane-d4 (Surr)	103		% Recovery	EPA 8260B	09/30/2005
TPH as Diesel	94	50	ug/L	M EPA 8015	09/30/2005
Octacosane (Diesel Surrogate)	117		% Recovery	M EPA 8015	09/30/2005

Approved By:



Project Name :

Tipple Motors

Project Number: 3034.01

Sample Date :09/22/2005

Sample: MW-7

Matrix: Water

Lab Number: 46153-07

Report Number: 46153 Date: 10/03/2005

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Toluene	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Diisopropyl ether (DIPE)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	09/30/2005

TPH as Gasoline	< 50	50	ug/L	EPA 8260B	09/30/2005
1,2-Dichloroethane	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
1,2-Dibromoethane	< 0.50	0.50	ug/L	EPA 8260B	09/30/2005
Toluene - d8 (Surr)	99.3		% Recovery	EPA 8260B	09/30/2005
4-Bromofluorobenzene (Surr)	98.7		% Recovery	EPA 8260B	09/30/2005

Dibromofluoromethane (Surr)

1,2-Dichloroethane-d4 (Surr)

103

% Recovery

EPA 8260B

EPA 8260B

TPH as Diesel

< 50

50

ug/L

M EPA 8015

109

ug/L M EPA 8015 09/29/2005

Octacosane (Diesel Surrogate)

% Recovery M EPA 8015

09/29/2005

09/30/2005

09/30/2005

Approved By:

Joel Kiff



Project Name: **Tipple Motors**

Project Number: 3034.01

Sample: MW-8

Sample Date :09/22/2005

Report Number: 46153

Date: 10/03/2005

Matrix: Water

Lab Number: 46153-08

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	680	2.0	ug/L	EPA 8260B	09/30/2005
Toluene	58	2.0	ug/L	EPA 8260B	09/30/2005
Ethylbenzene	400	2.0	ug/L	EPA 8260B	09/30/2005
Total Xylenes	390	2.0	ug/L	EPA 8260B	09/30/2005
Methyl-t-butyl ether (MTBE)	< 2.0	2.0	ug/L	EPA 8260B	09/30/2005
Diisopropyl ether (DIPE)	440	2.0	ug/L	EPA 8260B	09/30/2005
Ethyl-t-butyl ether (ETBE)	< 2.0	2.0	ug/L	EPA 8260B	09/30/2005
Tert-amyl methyl ether (TAME)	< 2.0	2.0	ug/L	EPA 8260B	09/30/2005
Tert-Butanol	10	9.0	ug/L	EPA 8260B	09/30/2005
TPH as Gasoline	12000	200	ug/L	EPA 8260B	09/30/2005
1,2-Dichloroethane	170	2.0	ug/L	EPA 8260B	09/30/2005
1,2-Dibromoethane	< 2.0	2.0	ug/L	EPA 8260B	09/30/2005
Toluene - d8 (Surr)	92.5		% Recovery	EPA 8260B	09/30/2005
4-Bromofluorobenzene (Surr)	106		% Recovery	EPA 8260B	09/30/2005
Dibromofluoromethane (Surr)	102		% Recovery	EPA 8260B	09/30/2005
1,2-Dichloroethane-d4 (Surr)	94.4		% Recovery	EPA 8260B	09/30/2005
TPH as Diesel	< 3000	3000	ug/L	M EPA 8015	09/29/2005
Octacosane (Diesel Surrogate)	111		% Recovery	M EPA 8015	09/29/2005

Approved By:



Project Name: Tipple Motors

Project Number: 3034.01

Sample: BLDG-1A

Matrix: Air Lab Number: 46153-09 Sample Date :09/23/2005

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.050	0.050	ppmv	EPA 8260B	09/28/2005
Toluene	< 0.050	0.050	ppmv	EPA 8260B	09/28/2005
Ethylbenzene	< 0.050	0.050	ppmv	EPA 8260B	09/28/2005
Total Xylenes	< 0.050	0.050	ppmv	EPA 8260B	09/28/2005
TPH as Gasoline	< 5.0	5.0	ppmv	EPA 8260B	09/28/2005
Toluene - d8 (Surr)	97.9		% Recovery	EPA 8260B	09/28/2005
4-Bromofluorobenzene (Surr)	99.6		% Recovery	EPA 8260B	09/28/2005

Approved By:

Report Number: 46153 Date: 10/03/2005

QC Report : Matrix Spike/ Matrix Spike Duplicate

Report Number: 46153 Date: 10/03/2005

Project Name: Tipple Motors

Project Number: 3034.01

Parameter	Spiked Sample	Sample	Spike	Spike Dup.	Spiked Sample	Duplicate Spiked Sample	1 2	Analysis	Date	Spiked Sample Percent		Relative	Spiked Sample Percent Recov.	Relative Percent Diff.
TDU 00 DISCOL	1		0 0) diag	\ ainc		INIGII IOO	Arialyzed	Kecov.	Kecov.	<u>=</u>	Limit	Limit
	DISTILL DISTILL	000	000	1000	983	979	ng/L	M EPA 8015	9/29/05	98.3	6.76	0.449	70-130	25
TPH as Diesel	Blank	<50	1000	1000	975	1050	ng/L	M EPA 8015	9/30/02	97.5	105	7.33	70-130	25
Benzene	46185-01	<0.50	40.0	40.0	40.3	38.9	J/bn	EPA 8260B	9/29/05	101	97.3	3.53	70-130	25
Toluene	46185-01	<0.50	40.0	40.0	39.1	38.3	ug/L	EPA 8260B	9/29/05	7.79	95.6	2.00	70-130	25
Tert-Butanol	46185-01	<5.0	200	200	230	226	ng/L	EPA 8260B	9/29/05	115	113	1 50	70-130	25
Methyl-t-Butyl Ether 46185-01	r 46185-01	<0.50	40.0	40.0	37.4	37.7	ng/L	EPA 8260B	9/29/05	93.6	94.4	0.809	70-130	25
Benzene	46161-01	1.0	40.0	40.0	37.2	36.1	ng/L	EPA 8260B	9/29/05	90.4	87.8	2 92	70-130	ر م
Toluene	46161-01	0.86	40.0	40.0	36.4	35.1	/gn	FPA 8260R	9/20/05	α	01.0 0F.7	10.0	707	2 1
Tert-Butanol	46161-01	11000	200	200	10900	10800	rg/L ua/L	EPA 8260B	9/29/05	0.00	03.7 27.3	3.32 108	70-130	22 25
Methyl-t-Butyl Ether 46161-01	r 46161-01	37	40.0	40.0	73.9	74.0	ng/L	EPA 8260B	9/29/05	91.8	92.0	0.187	70-130	25 25
Benzene	46186-03	<0.50	40.0	40.0	40.1	38.2	ug/L	EPA 8260B	9/30/05	100	92.6	4.66	70-130	25
I oluene	46186-03	<0.50	40.0	40.0	32.0	30.6	ng/L	EPA 8260B	9/30/02	80.1		4.60	70-130	25
l ert-butanol	46186-03	<5.0 5.0	200	200	181	179	ng/L	EPA 8260B	9/30/02	90.7	9.68	1.18	70-130	25
Metnyl-t-Butyl Ether 46186-03	. 46186-03	<0.50	40.0	40.0	45.8	43.8	ng/L	EPA 8260B	9/30/02	114	109	4.55		25

Approved By: Joe Kiff

KIFF ANALYTICAL, LLC

QC Report : Laboratory Control Sample (LCS)

Report Number: 46153 Date: 10/03/2005

Project Name: Tipple Motors

Project Number: 3034,01

Parameter	Spike Level	Units	Analysis Method	Date Analyzed	LCS Percent Recov.	LCS Percent Recov. Limit
Benzene	40.0	ng/L	EPA 8260B	9/29/05	102	70-130
Toluene	40.0	ng/L	EPA 8260B	9/29/05	96.5	70-130
Tert-Butanol	200	ng/L	EPA 8260B	9/29/05	112	70-130
Methyl-t-Butyl Ether	40.0	ng/L	EPA 8260B	9/29/05	93.0	70-130
Benzene	40.0	ng/L	EPA 8260B	9/29/05	91.0	70-130
Tolnene	40.0	ng/L	EPA 8260B	9/29/05	93.0	70-130
Tert-Butanol	200	ng/L	EPA 8260B	9/29/05	100	70-130
Methyl-t-Butyl Ether	40.0	ug/L	EPA 8260B	9/29/05	8.68	70-130
Benzene	40.0	ng/L	EPA 8260B	9/30/02	99.2	70-130
Toluene	40.0	ng/L	EPA 8260B	9/30/02	84.7	70-130
Tert-Butanol	200	ng/L	EPA 8260B	9/30/02	8.06	70-130
Methyl-t-Butyl Ether	40.0	ng/L	EPA 8260B	9/30/02	112	70-130

Approved By: Joel Kiff

2795 2nd St, Suite 300 Davis, CA 95616 530-297-4800

KIFF ANALYTICAL, LLC

QC Report: Method Blank Data

Report Number: 46153 Date: 10/03/2005

Project Name: Tipple Motors

Project Number: 3034.01

	Measured	Method Reporting	þ	Analysis	Date			Method		•	ı
Parameter	Value	Limit	Units	Method	Analyzed	Parameter	ivieasured Value	Keporting	g Unifs	Analysis	Date Analyzed
TPH as Diesel	< 50	20	ng/L	M EPA 8015	09/29/2005	Benzene	< 0.50	0.50	ua/L	FPA 8260B	09/29/2005
Octacosane (Diesel Surrogate)	110		%	M EPA 8015	09/29/2005	Toluene	< 0.50	0.50	na/L	EPA 8260B	09/29/2005
						Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	09/29/2005
TPH as Diesel	< 50	20	ng/L	M EPA 8015	09/30/2005	Total Xylenes	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005
Octacosane (Diesel Surrogate)	114		%	M EPA 8015	EPA 8015 09/30/2005	Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005
1						Diisopropyl ether (DIPE)	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005
Benzene	< 0.050	0.050	ppmv	EPA 8260B	09/28/2005	Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005
Toluene	< 0.050	0.050	ppmv	EPA 8260B	09/28/2005	Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	09/29/2005
Ethylbenzene	< 0.050	0.050	ppmv	EPA 8260B	09/28/2005	Tert-Butanol	< 5.0	5.0	ng/L	EPA 8260B	09/29/2005
Total Xylenes	< 0.050	0.050	bpmv	EPA 8260B	09/28/2005	TPH as Gasoline	< 50	50	ug/L	EPA 8260B	09/29/2005
TPH as Gasoline	< 5.0	9.0	ppmv	EPA 8260B	09/28/2005	1,2-Dichloroethane	< 0.50	0.50	na/L	EPA 8260B	09/29/2005
Toluene - d8 (Surr)	98.0		%	EPA 8260B	09/28/2005	1,2-Dibromoethane	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005
4-Bromofluorobenzene (Surr)	9.96		%	EPA 8260B	09/28/2005	Toluene - d8 (Surr)	97.6		' %	EPA 8260B	09/29/2005
ŧ						4-Bromofluorobenzene (Surr)	110		%	EPA 8260B	09/29/2005
Benzene	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005	Dibromofluoromethane (Surr)	99.5		%	EPA 8260B	09/20/2006
Toluene	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005	1.2-Dichloroethane-d4 (Surr)	1 80		2 %	00000 400	00/00/00
Ethylbenzene	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005		- - -		e	EFA 6260B	09/29/2005
Total Xylenes	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005	Benzene	< 0.50	0.50	na/L	FPA 8260B	09/30/2005
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005	Toluene	< 0.50	0.50	na/L	EPA 8260B	09/30/2005
Diisopropyl ether (DIPE)	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005	Ethylbenzene	< 0.50	0.50	ng/L	EPA 8260B	09/30/2005
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005	· Total Xylenes	< 0.50	0.50	ng/L	EPA 8260B	09/30/2005
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005	Methyl-t-butyl ether (MTBE)	< 0.50	0.50	חמ/ן	FPA 8260B	10/30/30/5
l ert-Butanol	< 5.0	5.0	ng/L	EPA 8260B	09/29/2005	Diisopropyl ether (DIPE)	< 0.50	0.50	na/L	EPA 8260B	09/30/2005
TPH as Gasoline	< 50	50	ng/L	EPA 8260B	09/29/2005	Ethyl-t-butyl ether (ETBE)	< 0.50	0.50		EPA 8260B	09/30/2005
1,2-Dichloroethane	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005	Tert-amyl methyl ether (TAME)	< 0.50	0.50		EPA 8260B	09/30/2005
1,2-Dibromoethane	< 0.50	0.50	ng/L	EPA 8260B	09/29/2005	Tert-Butanol	< 5.0	5.0	ng/L	EPA 8260B	09/30/2005
Toluene - d8 (Surr)	100		%	EPA 8260B	09/29/2005	TPH as Gasoline	< 50	50	ng/L	EPA 8260B	09/30/2005
4-Bromofluorobenzene (Surr)	101		%	EPA 8260B	09/29/2005	Toluene - d8 (Surr)	85.3		%	EPA 8260B	09/30/2005
Dibromofluoromethane (Surr)	111		%	EPA 8260B	09/29/2005	4-Bromofluorobenzene (Surr)	100			EPA 8260B	09/30/2005
1,2-Dichloroethane-d4 (Surr)	103		%	EPA 8260B	09/29/2005						2007/20160

Approved By: Joel Kiff

KIFF ANALYTICAL, LLC

For Lab Use Only 5 60 20 00 90 00 60 Yes/ No Coolant Presen 0 ಕ □ 12 14 14 □ Z Pr M □ \(\frac{4}{2} \) Chain-of-Custody Record and Analysis Request Therm. ID# エアノ CO 3 Sample Receipt Regardless of Lot time W.E.T. Leed (STLC) Hime 1505 Total Lead (EPA 6010) (M2108 AGE) IIO 1010M 88 HQ1 Analysis Request (M2108 A93) leseid as H9T For Lab Use Only: 202160 Date Volatile Organics (EPA 524.2 Drinking Water) Volatile Organics Full List (EPA 8260B) Volatile Halocarbons (EPA 8260B) Initials eed Scav.(1,2 DCA & 1,2 EDB-EPA 8260B) 17100 ල් Oxygenates (EPA 8260B) Oxygenates (EPA 8260B) Temp C Remarks: TPH Gas (EPA 8260B) 3.5 8 5 5 (B0928 A93) X3TB MTBE (EPA 8260B) @ 0.5 ppb SRG # / Lab No. MTBE (EPA 8260B) per EPA 8021 level 🧔 5.0 ppb Matrix TLA. **≥** llos lechnesite e transferioristant **Vater** Global ID: 70603300046 Preservative ES (S) EDF Deliverable To (Email Address) Received by Laboratory: Jasoy NKLyn euoN Sampling Company Log Code: Sampler Signature: CONH HCI Received by: California EDF Report? 2795 2nd Street Suite 300 Davis, CA 95616 Lab: 530,297.4800 Fax: 530,297.4802 Telbel Container GISSS ن س 1205/ Ime E YIOH Sleave 2/26/15 AOV Im 04 4:20X 75.2 207260 3:10 12.30 7:45 Time 830 Shiloh Rd., Building 44, Suite J, Windsor, CA 95492 Sampling Date Date Sycyb R/2365 Date Motors roject Contact (Hardcopy or PDF To): P.O. # Fax#: Project Name: Distribution: White - Lab; Pink - Originator Rev: 051805 Sample Designation Project #: 3034.0 NIX-14 Ferndale, (A ME 1 80 4-MW MW-6 Company / Address: MW-4 カーダし Project Address: 534 Malko St 13X 1 3 X M8-`\ Z|X (707) 575-8622 Brian Hasik Relinquished by: Relinquished Phone #:



Air Toxics Ltd. Introduces the Electronic Report

Thank you for choosing Air Toxics Ltd. To better serve our customers, we are providing your report by e-mail. This document is provided in Portable Document Format which can be viewed with Acrobat Reader by Adobe.

This electronic report includes the following:

- Work order Summary;
- · Laboratory Narrative;
- · Results; and
- · Chain of Custody (copy).

AN ENVIRONMENTAL ANALYTICAL LABORATORY

WORK ORDER #:

0509579

Work Order Summary

CLIENT:

Mr. Scott Forbes

Kiff Analytical

2795 2nd Street

Suite 300

Davis, CA 95616

PHONE: FAX:

530-297-4808

DATE RECEIVED:

DATE COMPLETED:

530-297-4800

PROJECT#

3034.01 Tipple Motors

Kiff Analytical

2795 2nd Street

Davis, CA 95616

Suite 300

09/27/2005

10/03/2005

CONTACT:

P.O. #

BILL TO: Mr. Scott Forbes

46153

Nicole Danbacher

			RECEIPT
FRACTION #	NAME	<u>TEST</u>	VAC./PRES.
01A	MW-2A	Modified ASTM D-1946	Tedlar Bag
01AA	MW-2A Duplicate	Modified ASTM D-1946	Tedlar Bag
02A	Lab Blank	Modified ASTM D-1946	NA
03A	LCS	Modified ASTM D-1946	NA

CERTIFIED BY:

Sinda d. Fruma.

10/03/05 DATE:

Laboratory Director

Certfication numbers: AR DEQ - 03-084-0, CA NELAP - 02110CA, LA NELAP/LELAP- AI 30763, NJ NELAP - CA004 NY NELAP - 11291, UT NELAP - 9166389892

Name of Accrediting Agency: NELAP/Florida Department of Health, Scope of Application: Clean Air Act, Accreditation number: E87680, Effective date: 07/01/05, Expiration date: 06/30/06

Air Toxics Ltd. certifies that the test results contained in this report meet all requirements of the NELAC standards

This report shall not be reproduced, except in full, without the written approval of Air Toxics Ltd.

180 BLUE RAVINE ROAD, SUITE B FOLSOM, CA - 95630 (916) 985-1000 . (800) 985-5955 . FAX (916) 985-1020

LABORATORY NARRATIVE Modified ASTM D-1946

Kiff Analytical Workorder# 0509579

One 1 Liter Tedlar Bag sample was received on September 27, 2005. The laboratory performed analysis via Modified ASTM Method D-1946 for Carbon Dioxide using GC/TCD. The method involves direct injection of 1.0 mL of sample.

Method modifications taken to run these samples include:

Requirement	ASTM D-1946	ATL Modifications
Calibration	A single point calibration is performed using a reference standard closely matching the composition of the unknown.	A 3-point calibration curve is performed. Quantitation is based on a daily calibration standard which may or may not resemble the composition of the associated samples.
Reference Standard	The composition of any reference standard must be known to within 0.01 mol % for any component.	The standards used by ATL are blended to a >/= 95% accuracy.
Sample Injection Volume	Components whose concentrations are in excess of 5 % should not be analyzed by using sample volumes greater than 0.5 mL.	The sample container is connected directly to a fixed volume sample loop of 1.0 mL on the GC. Linear range is defined by the calibration curve. Bags are loaded by vacuum.
Normalization	Normalize the mole percent values by multiplying each value by 100 and dividing by the sum of the original values. The sum of the original values should not differ from 100% by more than 1.0%.	Results are not normalized. The sum of the reported values can differ from 100% by as much as 15%, either due to analytical variability or an unusual sample matrix.
Precision	Precision requirements established at each concentration level.	Duplicates should agree within 30% RPD for detections > 5 X's the RL.

Receiving Notes

Sample was received past the recommended hold time of 3 days. The discrepancy was noted in the Sample Receipt Confirmation email/fax and the analysis proceeded.

Analytical Notes

There were no analytical discrepancies.

Definition of Data Qualifying Flags

Seven qualifiers may have been used on the data analysis sheets and indicate as follows:

- B Compound present in laboratory blank greater than reporting limit.
- J Estimated value.
- E Exceeds instrument calibration range.
- S Saturated peak.
- Q Exceeds quality control limits.
- U Compound analyzed for but not detected above the detection limit.
- M Reported value may be biased due to apparent matrix interferences.

File extensions may have been used on the data analysis sheets and indicates as follows:

- a-File was requantified
- b-File was quantified by a second column and detector
- r1-File was requantified for the purpose of reissue

Client Sample ID: MW-2A Lab ID#: 0509579-01A

NATURAL GAS ANALYSIS BY MODIFIED ASTM D-1946

File Name; Dil. Factor:	9092722b 1.00		Date of Collection: 9/2 Date of Analysis: 9/27	and the same of th
Compound		Rpt. Limit (%)		Amount (%)

0.010

13

Container Type: 1 Liter Tedlar Bag

Carbon Dioxide

Client Sample ID: MW-2A Duplicate

Lab ID#: 0509579-01AA

NATURAL GAS ANALYSIS BY MODIFIED ASTM D-1946

Compound		Rpt. Limit	Amount
Dil. Factor:	9092723b 1.00	The second of	of Collection: 9/23/05 of Analysis: 9/27/05 04:10 PM

0.010

13

Container Type: 1 Liter Tedlar Bag

Carbon Dioxide

Client Sample ID: Lab Blank Lab ID#: 0509579-02A

NATURAL GAS ANALYSIS BY MODIFIED ASTM D-1946

File Name: Dil. Factor:	9092703 1.00		Date of Collection: NA Date of Analysis: 9/27/05 08:13 AM
Compound		Rpt. Limit (%)	Amount (%)
Carbon Dioxide		0.010	Not Detected

Container Type: NA - Not Applicable

Client Sample ID: LCS

Lab ID#: 0509579-03A

NATURAL GAS ANALYSIS BY MODIFIED ASTM D-1946

File Name;	9092724	Date of Collection: NA
Dil. Factor:	1,00	Date of Analysis: 9/27/05 04:34 PM

Compound%RecoveryCarbon Dioxide100

Container Type: NA - Not Applicable

		1 4	uest	•		30-						daJ.		··· =													S OF					
		Page ⊥ of	Red	 		daQ enb		2	00	ፘ '	_ Հ դ	əqo:	рC	ļ	>	۱											ES			ı		-
		Pa	Chain-of-Custody Record and Analysis Request	3																							OK TO RUN TEST REGARDLESS OF					0 4 9 0 4 0
		No.	ecord and			uest								•													RUN TES				Accounts Payable	<u> </u>
	e e E3	Lab No.	ustody R	1		Analysis Request										-							NTACE					HOLD TIME.			Account	;
	Air Toxics 180 Blue Ravine Rd, Suite B Folsom, CA 95630	tel: 916-985-1000	ain-of-C			Ā	-																CLISTODY SEAL INTACT?	NONE TEMP			Remarks:	로	<u> </u>		Dill be:	
	Air Toxics Ravine Ro om, CA 95	916-9	ວັ		L,					=1				² 00	×	ĺ	,						CEST	X						i	9/22/8	3
	Blue Fols	堊	ç		:	PENDING						Matrix		AIR SOIL	Ī	(-		, <u>-</u>			1						9/2	`
l	₹		Yes		Recommended but not mandatory to complete this section:	PEN	046	يَّ ا				H	H	∃TAW	-	T					+					\vdash					An	
İ	300		×.		elelumo:	:ap	T0602300046	EDF Deliverable to (Email Address):	_			Preservative		AONE GE	<u> </u>	1					1					ļ		[
l	Suite		ı		tory to	03 Ec	090	IB!!	8		Loo.	rese		CONH		İ							-				-			Received by Laboratory:	C177.43 W. Day	
	20 a 60	9	£		manda	rıy [r]	-		/ical					HCI	_	_			_		1] 		١	V ab	, A	
	4 St 35611 37.48	₽ =	ď		ut net	ести		흝	ınalı		inak	힐		TEDL Meseus	+	+	\dashv			+-	4	_		<u> </u>		+			ved 5	မြွ		
l	9.5 2.5 2.5 3.5 5.5 5.5 5.5 5.5 5.5 5.5 5.5 5.5 5	2 2	ď		A popu	ğ	ق	i e	SKIII.	P	X.	Container		edmi	1	1	1	-		i	+					H	Received by:		Received by:	e Sej	\$	
	2795 Second Street, Suite 300 Davis, CA 95616 Lab: 530.297.4800	장 장	EDF Report?		эсстион	Sampling Company Log Code;	Global ID:	DF DE	inbox@kiffanalyti ca l.com	E-mail address:	inbox@kiffanalytical.com	ਤੌ	Jer	Glass Poly			4				1					Ļ		3	ewi	E		
	CV ET . TH		=		K N						, <u>=</u>			<u>ال</u>	i z	į					Ì	elegge -						2500		Date		
			n n						46153			Sampling		Cate	9/23/05													大部个自己的				A 1
(r PUF to)	Scott Forbes			FAX No.:	P.O. No.:					T		0,	T										ļ	Į į	スポイ				'
		֡֝֝֝֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓	rdcopy (Scott					3034.01																							
		7	et) tagu		4ddress:	lytical,		nber:	ö	.je:	lotors	irass:		ation													101.0	3 3 3	Ä	by:	.	
	Apalviscal IIC		Project Contact (Hardcopy or PDF to):		Company/Address:	Kiff Analytical, LLC	Phone No.:	Project Number:		Project Name:	Tipple Motors	Project Address:	Sample	Designation	MW-2A												Relinquisted	귉	Relinquist ed/y	Relinquished by:		
_			<u></u>		<u>~</u>		مك	<u> LL</u>		 	<u>, </u>	ഥ	100		-27					_	Ш.,						<u>oc</u>	_	מל.	100		